

RECOMMENDED SETTINGS for MOST USERS (do not use spooky2 boost)

KILLING PATHOGENS with BLK or WHT viaDNA REMOTE:

Select the spooky2 software **Settings** tab

In the **Signal Settings** box ... type in the **Amplitude** and **Offset** numbers for **Out1** and **Out2** ... remote light is **RED**

Read page **1** of **Amplitude, Power, Offset – Killing & Healing Graphs**

	Out 1	Out 2	
Duty Cycle	50	50	%
Amplitude	7	7	V
Offset	100	100	%
Phase	0	0	°

In the **Output Control** box ... select **Out1 fixed at ...** type in **2977792**

Output Control

Out 1 = 0 X 1) + 0 Hz
Swap Waveform Every 0 Seconds

Out 2 = (Out 1 X 1) + 0 Hz

Out 1 fixed at 2977792 Hz. Out 2 = Abs (Out1 - F1) Hz

Out 2 Follows Program Frequency

Out 2 Runs Every Second Frequency Swap Out 1 And Out 2

In the **Waveform Setup** box ... select **Square Waveform** for 1 and 2

Waveform Setup

1 2 Waveform

KILLING PATHOGENS in CONTACT MODE with Y-ADAPTER:

Select the spooky2 software **Settings** tab

In the **Signal Settings** box ... type in the **Amplitude** numbers for **Out1** and **Out2**

	Out 1	Out 2	
Duty Cycle	50	50	%
Amplitude	10	10	V
Offset	0	0	%
Phase	0	0	°

In the **Output Control** box ... select **Out1 fixed at ...** type in **2977792**

Output Control

Out 1 = 0 X 1) + 0 Hz
Swap Waveform Every 0 Seconds

Out 2 = (Out 1 X 1) + 0 Hz

Out 1 fixed at 2977792 Hz. Out 2 = Abs (Out1 - F1) Hz

Out 2 Follows Program Frequency

Out 2 Runs Every Second Frequency Swap Out 1 And Out 2

In the **Waveform Setup** box ... select **Square Waveform** for 1 and 2

Waveform Setup

1 2 Waveform

RECOMMENDED SETTINGS for MOST USERS (*do not use spooky2 boost*)

HEALING with BLK viaDNA REMOTE:

Select the spooky2 software **Settings** tab

In the **Signal Settings** box ... type in the **Amplitude** and **Offset** numbers for **Out1** and **Out2** ... remote light is **GREEN**

Read page **2** of **Amplitude, Power, Offset – Killing & Healing Graphs**

Signal Settings

	Out 1	Out 2	
Duty Cycle	50	50	%
Amplitude	9.9	9.9	V
Offset	-100	-100	%
Phase	0	0	°

Two green arrows point from the text above to the Amplitude and Offset values for Out 1 and Out 2.

In the **Output Control** box ... select **Out1 fixed at** ... type in **2977792**

Output Control

Out 1 = 0 X 1) + 0 Hz
Swap Waveform Every 0 Seconds

Out 2 = (Out 1 X 1) + 0 Hz

Out 1 fixed at 2977792 Hz. Out 2 = Abs (Out1 - F1) Hz

Out 2 Follows Program Frequency

Out 2 Runs Every Second Frequency Swap Out 1 And Out 2

In the **Waveform Setup** box ... select **Sine Waveform** for **1** and **2**

Waveform Setup

1 2 Waveform

The waveform display shows a sine wave for channel 1 and a square wave for channel 2.

SUBSTANCE SIMULATION (*digital drugs*) with BLK viaDNA REMOTE:

Select the spooky2 software **Settings** tab

In the **Signal Settings** box ... type in the **Amplitude** numbers for **Out1** and **Out2** ... remote light is **RED/GREEN**

Signal Settings

	Out 1	Out 2	
Duty Cycle	50	50	%
Amplitude	10	10	V
Offset	0	0	%
Phase	0	0	°

In the **Output Control** box ... select **Out2 Follows Program Frequency**

Output Control

Out 1 = 0 X 1) + 0 Hz
Swap Waveform Every 0 Seconds

Out 2 = (Out 1 X 1) + 0 Hz

Out 2 Follows Program Frequency

Out 2 Runs Every Second Frequency Swap Out 1 And Out 2

In the **Waveform Setup** box ... select **Sine Waveform** for **1** and **2**

Waveform Setup

1 2 Waveform

The waveform display shows a sine wave for channel 1 and a square wave for channel 2.